

Optimised hydrodynamics for membrane bioreactors with immersed flat sheet membrane modules

H. Prieske^{a*}, L. Böhm^a, A. Drews^b, M. Kraume^a

^a*Technische Universität Berlin, Chair of Chemical and Process Engineering, Straße des 17. Juni 135, 10623 Berlin, Germany
email: h.prieske@mailbox.tu-berlin.de, matthias.kraume@tu-berlin.de*

^b*University of Oxford, Dept. of Engineering Science, Parks Rd, Oxford OX1 3PJ, UK*

Received 3 June 2009; Accepted 4 January 2010

ABSTRACT

Since aeration is the largest cost factor in membrane bioreactor (MBR) operation it is clear that the biggest leap towards energy and operational costs savings can be achieved by improving the use of air. Many basics of the complex two-phase flow in membrane modules and in the overall MBR tank as well as their interactions, however, are still poorly understood. This work focuses both on fundamental studies on shear stress exerted by rising bubbles and on optimising the geometries of tank and module accordingly in order to obtain an improved deposition control at minimum energy input. For both, parameter studies were carried out by numerical simulations which were validated with experimental measurements. The optimum bubble size/channel width combination depended on the superimposed liquid velocity. The relationship between the liquid circulation velocity and the aeration intensity was measured for different reactor and module geometries. A modification of the Chisti model for airlift loop reactors was also performed which can be used as a design rule for tank and module geometry or aeration rate. At the same gas flow rate, a 30–50% increase in liquid circulation velocity was achieved by a simple modification of the sparger and the entry zone to the riser section.

Keywords: Air scour; Fouling; Hydrodynamic optimisation; MBR design; Shear stress; Single bubble

* Corresponding author.