

Desalination and Water Treatment

www.deswater.com

1944-3994/1944-3986 © 2012 Desalination Publications. All rights reserved doi: 10.1080/19443994.2012.696803

47 (2012) 105–111 September



Recovery of palladium(II) from acidic chloride solution using kerosene containing tri-n-octyl/decyl amine (Alamine 336)

Chen-Yu Peng, Teh-Hua Tsai*

Department of Chemical Engineering and Biotechnology, National Taipei University of Technology, Taipei 10608, Taiwan, ROC Tel. +886 2 27712171x2543; email: thtsai@ntut.edu.tw

Received 29 September 2011; Accepted 8 March 2012

ABSTRACT

This study employed a tri-n-octyl/decyl amine (Alamine 336) as an extractant dissolved in kerosene to extract palladium(II) from HCI solution at 25 °C. The experiments of different stripping reagents such as HCI, NaCl, KCl, BaCl₂, AlCl₃, and thiourea were compared, respectively; and the optimal status was determined. The results showed that the extraction distribution ratios are proportional to the extractant concentration and disproportional to chloride ion concentration. By graphical analysis, the compositions of palladium complexes in organic phase and equilibrium constant of recovered extraction reaction were examined. Finally, the recovery efficiency of palladium(II) in acidic chloride solution was determined.

Keywords: Solvent extraction; Stripping; Alamine 336; Palladium

^{*}Corresponding author.

Challenges in Environmental Science and Engineering, CESE 2011 25–30 September 2011, Tainan City, Taiwan